

G-SNACK

G-SNACK



	G-Snack Master 6°C	G-Snack FOOD Master 2°C	G-Snack Slave 6°C	G-Snack FOOD Slave 2°C
No. of selections	56	56	56	56
No. of shelves	7	7	7	7
H x W x D (mm)	1830 x 955 x 850	1830 x 955 x 850	1830 x 805 x 850	1830 x 805 x 850
Weight (in KG)	310 kg	310 kg	245 kg	245 kg
Control	Executive: MDB	Executive: MDB	Executive: MDB	Executive: MDB
Temperature control	by thermostat	Electronic with digital display	by thermostat	Electronic with digital display
Temperature range	6-25°C	2°C-25°C	6-25°C	2°C-25°C
Power consumption	400W	550W	350W	500W
Power Supply	230 V / 50 Hz	230 V / 50 Hz	230 V / 50 Hz	230 V / 50 H

Standard cabinet colours



Standard ABS panel colour



Option:

Customized cabinet/ABS colour on request

Branding on ABS in silk screen print

Double spiral motor

Various product fitting kits



Perishable Product Area
2°C

For further information, please contact:



SandenVendo Europe S.p.A.
Reg. Cavallino, 2 | Coniolo 15030 (AL) | Italy
Tel.: +39 0142 335 111 | Fax: +39 0142 562 348
www.sandenvendo.it | E-Mail: marketing@sandenvendo.it

Specifications subject to change | November 2008

Snack Revolution

G-SNACK Snack Revolution

Design & Features

SandenVendo presents the new line of spiral merchandiser "G Snack". This new line has the best technical features required in the market, low energy consumption, wide customized color option, a patented coupling system for easy positioning of spirals, yet offered at a very competitive price! G-Snack is available both Master and Slave versions. Master offers a possibility to install a speedy elevator for safe and swift delivery of the products. The internal temperature can be set at 2°C with 2 different cooling solutions (below).



Food area height is adjustable



Advanced Software Programming


Our Advanced SOFTWARE allow the machine programmed in Energy Saving modes.

LIGHT CONTROL

TURNED OFF - when the machine is NOT in function, according to the set value of the program. (Set-up can be done by the days of the week, start and stop time, also with "during not-vending period").

SAFETY HEALTH CONTROL

When the temperature stays over the set temperature for more than 30 min. sales will be blocked. (Programmable on the selected shelves, which cover all the lower shelves).



Guaranteed Temperature Function
to offer product safety for the consumers

SPEEDY ELEVATOR

Delicate and/or fragile products can be sold also eye-height position! Speedy delivery of the products is guaranteed!



BANKABLE




PATENTED

COUPLING SYSTEM for easy spiral orientation

The spiral can be easily positioned in 8 angles, without taking out or pull it. Simply turn the spiral to set the ideal position. We are the first and only one to introduce this innovation in the market!

Easy and quick; clip-in, clip-out!



REMOVABLE DELIVERY EYELET

A unique feature, a completely removable delivery eyelet. Easy access in case of maintenance and cleaning!



SECURITY



Option

